

# 24 Volt ASi-5/ASi-3 Gateway in stainless steel, 1 ASi-5/ASi-3 Master

**ASi-5 – Great data bandwidth, short cycle times**

**Compatible with all ASi generations**

**ASi-5 master and ASi-3 master in one device**

**24 Volt ASi:**

- The device can be operated directly on a 24 V (PELV) power supply.
- With integrated data coupling coils and adjustable self-resetting fuses optimized for safe use also of powerful 24 V power supplies.

**Available fieldbus interfaces:**

- PROFINET IO: IRT-technology and 1 integrated Switch

**OPC UA interface and REST API for IIoT applications**

**Integrated web server for simple diagnostics and maintenance**


**Recognition of duplicate ASi addresses**

**ASi Noise Detector integrated**



(figure similar)



Figure	Interface, fieldbus <sup>(1)</sup>	ASi-5/ASi-3	Number of ASi networks, number of ASi Master <sup>(2)</sup>	Integrated decoupling, ASi current measurement in the gateway <sup>(3)</sup>	Recognition of duplicate ASi addresses <sup>(4)</sup>	ASi fault detector <sup>(5)</sup>	Programming in C <sup>(6)</sup>	Article no.
	PROFINET, OPC UA	ASi-5 + ASi-3 compatible	1 ASi network, 1 ASi-5/ASi-3 Master	yes, max. 4 A/ASi network	yes	yes	no	<b>BWU3847</b>

**(1) Interface, fieldbus**

Communication interface between fieldbus and gateway: interfaces for standardized fieldbus systems in industrial automation.  
**OPC UA server:** interface for the OPC UA communication.

**The latest version of the device description file of the gateway is available in the "Downloads" section of the respective device.**

**(2) Number of ASi networks, number of ASi Master**

**"Single Master":** 1 ASi network, 1 ASi-5/ASi-3 Master.

**(3) Integrated decoupling, ASi current measurement in the gateway**

**"yes, max. 4 A/ASi network":** Data decoupling integrated in the gateway. Cost-effective power for 2 ASi networks with 1 power supply (optionally supply of multiple Single Gateways by 1 power supply). Operation with short cable lengths with standard 24 V power supply possible.

**(4) Recognition of duplicate ASi addresses**

Detects whether the same address has been assigned to two ASi nodes. Frequent error when using a handheld addressing device.

**(5) ASi fault detector**

Checks the ASi line for interference effects such as noise, external voltages, ...

**(6) Programming in C**

Using a C-program offers the possibility to run mini-PLC functions with a gateway.

## 24 Volt ASi-5/ASi-3 Gateway in stainless steel, 1 ASi-5/ASi-3 Master

<b>Article no.</b>	<b>BWU3847</b>
<b>Fieldbus Interface</b>	
Type	PROFINET 2 x RJ-45, integrated 2-Port-Switch IRT capability Conformance Class B integrated switch complies with Class C (IRT capability)
IT interface	OPC UA server, web server, REST API
Baud rates	100 MBaud
Variably configurable Assembly Objects	yes
Function	PROFINET IO Device Media Redundancy Protocol (MRP) Shared Device
Card slot	chip card (BW4055) for storage of configuration data
<b>ASi</b>	
ASi specification	ASi-5 + ASi-3
Cycle time	<b>Cycle time ASi-5 (constant):</b> 1,27 ms for 384 bits input data + 384 bits output data
	<b>Cycle time ASi-3 (variable):</b> 150 $\mu$ s * (number of ASi-3 nodes + 2)
Operating voltage	24 V <sub>DC</sub> (20 ... 31,6 V) (PELV voltage)
Operating current	approx. 250 mA
Current per ASi network	max. 4 A
Length of ASi cable	with 24 V power supply: max. 50 m with 30 V power supply: max. 100 m with ASi-3 / max. 200 m with ASi-5
<b>Display</b>	
LCD	menu, ASi indication of ASi addresses, error messages in plain text
LED power (green)	power ON
LED PROFINET	green: PROFINET communication active red: no PROFINET communication
LED config error (red)	configuration error
LED U ASi (green)	ASi voltage o.k.
LED ASi active (green)	ASi normal operation active
LED prg enable (green)	automatic address programming enabled
LED prj mode (yellow)	in configuration mode
<b>UL-specifications (UL508)</b>	
External protection	An isolated voltage source with a PELV/SELV voltage $\leq 30$ V <sub>DC</sub> must have internal or external current limiting.
In general	UL mark does not provide UL certification for any functional safety rating or aspects of the above devices.

## 24 Volt ASi-5/ASi-3 Gateway in stainless steel, 1 ASi-5/ASi-3 Master

<b>Article no.</b>	<b>BWU3847</b>
<b>Environment</b>	
Applied standards	EN 61131-2 EN 60529 EN 61000-6-2 EN 61000-6-4
Operating altitude	max. 2000 m
Operating temperature	-25 °C ... +55 °C
Storage temperature	-25 °C ... +85 °C
Housing	Stainless Steel, for DIN rail mounting
Pollution degree	2
Protection category	IP20
Tolerable loading referring to humidity	according to EN 61131-2
Maximum tolerable shock and vibration stress	according to EN 61131-2
Voltage of insulation	≥500 V
Weight	500 g
Dimensions (W / H / D in mm)	85 / 120 / 83

<b>Article no.</b>	<b>BWU3847</b>
<b>Data decoupling integrated in the gateway</b>	•
<b>Current measurement of the ASi circuits</b>	•
<b>Self-resetting fuses</b>	•
<b>Adjustable fuses</b>	-
<b>ASi earth fault monitor distinguishes between ASi cable and sensor cable</b>	-
<b>Cost-effective power for 2 ASi networks with 1 power supply</b>	•

### Accessories:

- Chip card, memory capacity 512 kB (art. no. BW4055)
- Bihl+Wiedemann Suite - Software for Configuration, Diagnostics and Commissioning (art. no. BW2902)
- PROFINET Master Simulators Licenses (art. no. BW4754, BW4755)
- Power supplies, e.g.: 30 V power supply, 4 A, 1 phase (art. no. BW4218), 30 V power supply, 8 A, 1 phase (art. no. BW4219), 30 V power supply, 8 A, 3 phases (art. no. BW4220), 30 V Power Supply, 16 A, 1 phase (art. no. BW4221), 30 V Power Supply, 16 A, 3 phases (art. no. BW4222) (for further power supply units visit [www.bihl-wiedemann.de/en/products/accessories/power-supplies](http://www.bihl-wiedemann.de/en/products/accessories/power-supplies))