

ASi-5/ASi-3 Address Programming Device

for addressing of
ASi modules of all ASi specifications up to ASi-5



(figure similar)

The **ASi-5/ASi-3 handheld address programming device** is a compact device used for addressing ASi modules of all ASi specifications (2.0, 2.1, 3.0 and ASi-5).

The electromechanical connection takes place via one of the two addressing plugs that allow the addressing of ASi modules of specification 2.0 to ASi-5.

The scope of delivery includes the ASi-5/ASi-3 handheld address programming device, the USB-A to USB-C recharger cable and the addressing cables for addressing ASi-5 or ASi-3 modules (all connecting cables can be ordered as accessories).

Article no.	BW4925
Application	commissioning
Indication	color display (RGB OLED)
Buttons	membrane keyboard with 6 keys
Interface/connection	<ul style="list-style-type: none"> • 1 x connection for jack plug • 1 x connection for barrel plug • 1 x USB-C connection short circuit and overload protected
Power Supply ⁽¹⁾	via supercapacitor charging time: fully charged in approx. 30 min, sufficient for ≥120 read/write operations, approx. 10 min of charging is sufficient to allocate 70 ASi addresses (e.g. AB, single, ASi-5)
Operating voltage	5 V _{DC}
Operating time	≥ 120 read/write operations with a fully charged supercapacitor
Protection category according to EN 60529	IP20
Operating temperature	0 °C ... +50 °C
Storage temperature	-20 °C ... +55 °C
Weight	approx. 140 g (without cables)
Dimensions (W / H / D) in mm	60 / 130 / 35
Scope of delivery	<ul style="list-style-type: none"> • ASi-5/ASi-3 address programming device (BW4708) • ASi-5 addressing cable, jack plug to jack plug, 1.5 m (BW4711) • ASi-3 addressing cable, barrel plug to barrel plug, 1.5 m (BW4712) • Recharger cable USB-A to USB-C, 1 m (BW4713) • ASi-5/ASi-3 addressing cable, barrel plug to connecting wires, 1.5 m (BW4731) • ASi-5/ASi-3 addressing cable, barrel plug to M12 cable socket, straight, 5 poles, 1.5 m (BW4732)

⁽¹⁾ Power supply via Recharger cable USB-A to USB-C (BW4713).

Plug-in recharger USB-A for 115 V/230 V (BW4714) is sold separately (see accessories).

Accessories

- **ASi-5 addressing cable, jack plug to jack plug, 1.5 m (BW4711)**
- **ASi-3 addressing cable, barrel plug to barrel plug, 1.5 m (BW4712)**
- **Recharger cable USB-A to USB-C, 1 m (BW4713)**
- **Plug-in recharger USB-A for 115 V/230 V (BW4714)**
- **ASi-5/ASi-3 addressing cable, barrel plug to connecting wires, 1.5 m (BW4731)**
- **ASi-5/ASi-3 addressing cable, barrel plug to M12 cable socket, straight, 5 poles, 1.5 m (BW4732)**